

Rec'd PCT Int'l 10/5 27 APR 2005
10/5 32881

532881

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
13 May 2004 (13.05.2004)

PCT

(10) International Publication Number
WO 2004/039505 A1

(51) International Patent Classification⁷: B05C 5/02, 11/06

TAKAGI, Hiroyuki [JP/JP]; c/o Nordson Kabushiki Kaisha, Toshin Building 8 Floor, 5-21, Katsushima 1-chome, Shinagawa-ku, Tokyo 140-0012 (JP).

(21) International Application Number:
PCT/JP2003/013698

(74) Agents: OKABE, Masao et al.; No. 602, Fuji Bldg., 2-3, Marunouchi 3-chome, Chiyoda-ku, Tokyo 100-0005 (JP).

(22) International Filing Date: 27 October 2003 (27.10.2003)

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2002-314330 29 October 2002 (29.10.2002) JP

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


(71) Applicant (for all designated States except US): NORD-SON CORPORATION [US/US]; 28601 Clemens Road, Westlake, OH 44145-1119 (US).

Published:

— with international search report

[Continued on next page]

(54) Title: METHOD OF APPLYING VISCOUS FLUID MATERIAL AND APPARATUS THEREFOR



(57) Abstract: A method of applying a viscous fluid material for preventing a viscous fluid material (40) from accumulating on a contact type slot nozzle (30) when applying the viscous fluid material (40) onto an object to be applied (50) which has surface irregularities by using the contact type slot nozzle (30). The method of applying a viscous fluid material includes: moving the object (50) in a predetermined transport direction (X); bringing the nozzle (30) provided to a slot (35) into contact with the object (50) that is being moved; dispensing the viscous fluid material (40) from the slot (35) to apply the viscous fluid material (40) onto the object (50); and ejecting a heated compression gas on the downstream side of the slot (35) in the predetermined transport direction (X) to press the viscous fluid material (40) applied on the object (50) from the slot (35) against the object (50) by the ejected compression gas.

WO 2004/039505 A1